

# KITIGAWA LVC-1160 TEKNİK ÖZELLİKLER

<b>X travel</b>	1100 mm
<b>Y travel</b>	600 mm
<b>Z travel</b>	600 mm
<b>Distance from spindle nose to table surface</b>	150-750 mm
<b>Distance from spindle axis to column</b>	600 mm
<b>Guideway type(X, Y, Z)</b>	Roller Linear type RGW 35-45-45
<b>Ballscrew type (X, Y, Z)</b>	R40* P12 C3 Sınıf
<b>Table working area</b>	1200*600 mm
<b>Max. table load</b>	800 kg
<b>T Slot</b>	CD 100*18-4T
<b>Spindle type</b>	BT40 (Standart) BT50 (Opsiyonel)
<b>Spindle Motor</b>	11-15 kw
<b>Spindle R.P.M.</b>	10.000 r.p.m. (Standart) 12.000 - 15.000 r.p.m. (Opsiyonel)
<b>Spindle brand</b>	WLT,DH,Royal
<b>Rapid feed rates</b>	36.000-36.000-24.000 mm/min
<b>Cutting feed rates</b>	1-20.000 mm/min
<b>A.T.C. type &amp; capacity</b>	24 Tools Arm type A.T.C.
<b>Max. tool length</b>	250*89 mm
<b>Max. tool weight</b>	6 kg
<b>T-T change time</b>	3 sec.
<b>Pressurized air required</b>	4-6 kg/cm <sup>2</sup>
<b>Coolant tank capacity</b>	250L
<b>Machine dimension</b>	380*220*235 cm
<b>Machine Net weight</b>	7.000 kg